

AD706017


EXISTENCE OF X-PATHS IN ABSTRACT POLYTOPES

BY

ILAN ADLER, GEORGE DANTZIG, KATTA MURTY

TECHNICAL REPORT NO. 70-1

MARCH, 1970



*This document has been approved for public release and sale;
its distribution is unlimited.*

OPERATIONS
RESEARCH
HOUSE



Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va. 22151

Stanford
University
CALIFORNIA

EXISTENCE OF X-PATHS IN ABSTRACT POLYTOPES

by

ILAN ADLER, GEORGE DANTZIG, KATTA MURTY*

Technical Report No. 70-1

March, 1970

**Department of Operations Research
Stanford University
Stanford, California**

*** Department of Industrial Engineering
University of Michigan
Ann Arbor, Michigan**

Research and reproduction of this report was partially supported by Office of Naval Research, Contract N-00014-67-A0112-0011; U.S. Atomic Energy Commission, Contract AT[04-3] 326 PA#18; National Science Foundation, Grant GP 9329; U.S. Army Research Office, Contract DAHC04-67-0028; and National Institutes of Health, Grant GM 14789-G2.

Reproduction in whole or in part is permitted for any purpose of the United States Government. This document has been approved for public release and sale; its distribution is unlimited.

Given a finite set E of n symbols ($n \geq 2$), a family S of subsets of E (called vertices) form an abstract polytope (E, S) if the following three axioms are satisfied.

- [i] Each vertex is a subset of m symbols of E
($m \leq n$).
- [ii] Every subset of $m + 1$ symbols contains either
zero or two vertices.

Before stating the third axiom let us introduce two definitions.

Adjacency - Two vertices v^0 and v^* are said to be adjacent (or neighbors) if $v^0 \cup v^*$ has cardinality $m + 1$.

Path - A sequence of vertices v_1, \dots, v_k is called a path if v_i, v_{i+1} are adjacent for $i = 1, \dots, k-1$.

- [iii] Every pair of vertices v^0 and v^* can be joined by
a path $v^0 = v_1, \dots, v_k = v^*$ such that $v_i \subseteq v^0 \cup v^*$
 $i = 1, \dots, k$.

The dimension of (E, S) is defined as $n - m$, and the Graph of (E, S) is defined as the graph which is formed from the vertices of S and the arcs which join adjacent vertices.

Note that by axioms [i] and [ii] every vertex in (E, S) has exactly $n - m$ neighbors.

Theorem Given an abstract polytope (E, S) if two vertices v^0 and v^* in S each contain the same symbol (say x) there is an x -path joining them, i.e., there exists a path such that every vertex along the path contains x .

Abstract polytopes include as special cases simple convex polytopes. The latter can be represented as non-degenerate bounded feasible linear programs. The analogous theorem states: If two feasible bases have a column in common, then it is possible to pass from one to the other via a sequence of adjacent feasible basis changes all of which have ~~the column~~ in common. The usual proof is to assign as linear objective the maximization of the variable of the common column. Then two paths exist one from each of the initial feasible bases to an optimal basis. All bases along each path have the column in common. Hence if there is a unique optimal basis, the paths may be joined together to form a simple connecting path. It is not hard to extend the result to the non-unique case as well. For abstract polytopes, however, there are no basic variables nor an objective function, hence a different proof is required.

If Γ is any subset of E , we denote by $\text{card}(\Gamma)$, the cardinality of Γ .

Proof Case 1 - $\text{card}(v^0 \cup v^*) = m + 1$.

In this case v^0 and v^* are adjacent so v^0, v^* is an x -path joining v^0 and v^* .

Case 2 - $\text{card}(v^0 \cup v^*) = m + 2$.

Let $E^1 = v^0 \cup v^*$ and $S^1 = \{V \in S \mid V \subseteq E^1\}$. By axioms [1] -

[111], (E^1, S^1) is a 2-dimensional abstract polytope. Hence the graph G of (E^1, S^1) forms a simple cycle. Thus there are two separate paths joining v^0 to v^* . Suppose the theorem is false, i.e., in each of the two paths there exists a vertex (say v^1 and v^{11}) such that $x \notin v^1$ and $x \notin v^{11}$. But then $\text{card}(v^1 \cup v^{11}) \leq m+1$, so either $v^1 = v^{11}$ or v^1 is adjacent to v^{11} . Both cases contradict the cycle structure of G .

Therefore, at least one of the two paths joining v^0 and v^* is an x -path.

Case 3 - $\text{card}(v^0 \cup v^*) \geq m+3$.

Let $F = E - x$ and $R = \{V \in S \mid V \subset F\}$. If $R = \emptyset$ then obviously there exists an x -path joining v^0 and v^* (by axiom [111]). If $R \neq \emptyset$ then (F, R) is $n-m-1$ dimensional abstract polytope. By axiom [111] there exists a path $v^0 = v_1, \dots, v_k = v^*$ in S . If $v_i \notin R$ for all $i = 1, \dots, k$ then v_1, \dots, v_k is an x -path joining v^0 and v^* . If not, let f and l be, respectively, the first and last index i such that $v_i \in R$. Since (F, R) is an abstract polytope there exists a path $v_f = R_1, \dots, R_p = v_l$ such that $R_i \in R$ $i = 1, \dots, p$. Let S_1, \dots, S_p be respectively, the neighbors of R_1, \dots, R_p in $S-R$. (Note that every vertex in R has a unique neighbor in $S-R$, while a vertex in $S-R$ can be a neighbor of zero or several vertices in R .)

Since R_i, R_{i+1} ($i = 1, \dots, p-1$) differ by exactly one symbol it follows that the adjacent S_i and S_{i+1} (formed by adjoining the

common symbol x to R_1 and R_{i+1}) differ by at most two symbols.

Thus by cases 1 and 2, S_i and S_{i+1} ($i = 1, \dots, p-1$) can be joined by an x -path. So there is an x -path joining S_1 and S_p ; let us denote this x -path by $S_1 = \bar{S}_1, \dots, \bar{S}_q = S_p$.

It follows that $v^0 = v^1, \dots, v_{f-2}, \bar{S}_1, \dots, \bar{S}_q, v_{l+2}, \dots, v_k = v^*$ is an x -path joining v^0 and v^* .

Q.E.D.

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) Department of Operations Research Stanford University STANFORD, California		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE Existence of X-Paths in Abstract Polytopes		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Technical Report		
5. AUTHOR(S) (Last name, first name, initial) Adler, Ilan; Dantzig, George; Murty, Katta		
6. REPORT DATE March 1970	7a. TOTAL NO. OF PAGES 4	7b. NO. OF REFS -
8a. CONTRACT OR GRANT NO. N-00014-67-A-0112-0011	8b. ORIGINATOR'S REPORT NUMBER(S) Technical Report No. 70-1	
A. PROJECT NO. NR-047-064	9a. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES This document has been approved for public release and sale. Distribution of this document is unlimited.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Operations Research Program (code 434) Office of Naval Research WASHINGTON, D.C. 20306	
13. ABSTRACT → Given a finite set E of n symbols a family S of subsets of E (called vertices) form an <u>abstract polytope</u> if 1) Each vertex is a subset of m symbols of E . 2) Every subset of $m+1$ symbols of E contains either zero or two vertices (called adjacent). 3) Every pair of vertices V^0 and V^* can be joined by a path $V^0 = V_1, \dots, V_k = V^*$ such that V_i, V_{i+1} are adjacent and $V_i \subset V^0 \cup V^*$ $i = 1, \dots, k-1$. It is shown that if two vertices of a given abstract polytope contain the same symbol (say x) then there exists a path such that every vertex along the path contains x . → $V_{\text{sub } i}, V_{\text{sub } (i+1)}$ → $V_{\text{sub } \phi} = V_{\text{sub } 1}, \dots, V_{\text{sub } k} = V_{\text{sub } *}$ → $(V_{\text{sub } i})$ contained in $(V_{\text{sub } \phi})$ joined to $(V_{\text{sub } *})$		

DD FORM 1473
1 JAN 64

Unclassified
Security Classification

Unclassified
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Abstract Polytopes Linear Programming Polytopes						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.